



## RECOMMENDED OIL VISCOSITIES

AMBIENT TEMPERATURE	ISO VG	BASE OIL TYPE
UP THRU 40C (104F)	32	MINERAL OR SYNTHETIC
41C THRU 50C (105-122F)	68	SYNTHETIC ONLY

## APPROVED OIL SPECIFICATIONS FOR USE WITH ANTI-FRICTION BEARINGS

OIL MANUFACTURER	ISO VG 32		ISO VG 68	
	VISCOSITY: 130-165 SSU @ 100F		VISCOSITY: 284-347 SSU @ 100F	
	MINERAL BASE OIL	SYNTHETIC BASE OIL	MINERAL BASE OIL	SYNTHETIC BASE OIL
CHEVRON USA, INC	GST TURBINE OIL 32	TEGRA 32	GST TURBINE OIL 68	TEGRA 68
CONOCO OIL CO.	HYDROCLEAR TURBINE OIL 32	SYNCON 32	HYDROCLEAR TURBINE OIL 68	SYNCON 68
EXXON CO., USA	TERESSTIC 32	SYNNESTIC 32	TERESSTIC 68	SYNNESTIC 68
MOBIL OIL CO.	DTE OIL LIGHT	SHC 624	DTE OIL HEAVY MEDIUM	SHC 626
PENZOIL CO., INC	PENNZBELL TO 32	PENNZBELL SHD 32	PENNZBELL TO 68	PENNZBELL SHD 68
PHILLIPS PETROLEUM CO.	MAGNUS 32	SYNDUSTRIAL "E" 32	MAGNUS 68	SYNDUSTRIAL "E" 68
SHELL OIL CO.	TELLUS 32	TELLUS HD OIL AW SHF 32	TELLUS 68	TELLUS HD OIL AW SHF 68
TEXACO LUBRICANTS CO.	REGAL 32	CETUS PAO 32	REGAL 68	CETUS PAO 68